

## Standard mounting list for MIGUTAN expansion joint covers

joint covers	load bearing	HECO	gap [mm]
FP(G) 80/25	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 80/35	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 80/45	70KN-fork lift	MMS-plus F 7,5x80 VZ	350
FP(G) 80/60	30KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 80/80	30KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 80/95	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 80/115	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/25	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/35	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/45	70KN-fork lift	MMS-plus F 7,5x80 VZ	350
FP(G) 90/60	30KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/80	30KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/95	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 90/115	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/25	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/35	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/45	70KN-fork lift	MMS-plus F 7,5x80 VZ	350
FP(G) 110/60	300KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/80	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/95	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP(G) 110/115	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP 130/25	130KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP 130/35	70KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP 130/35	130KN-fork lift	MMS-plus F 7,5x80 VZ	350
FP 130/45	70KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FP 130/60	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP 130/80	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP 130/95	cars	MMS-plus SS 7,5x80 VZ	350
FP 130/115	cars	MMS-plus SS 7,5x80 VZ	350
FP 155/25	35KN-Stapler	MMS-plus SS 7,5x80 VZ	350
FP 155/35	35KN-Stapler	MMS-plus SS 7,5x80 VZ	350
FP 155/45	60KN-trucks	MMS-plus SS 7,5x80 VZ	350
FP 155/60	35KN-fork lift	Fischer RG M8x110	350
FP 155/80	35KN-fork lift	Fischer RG M8x110	350
FP 155/95	cars	Fischer RG M8x110	350
FP 155/115	cars	Fischer RG M8x110	350
FP(G) 80/60S	130KN-fork lift	Fischer RG M8x110	350
FP(G) 90/60S	130KN-fork lift	Fischer RG M8x110	350
FP(G) 110/60S	130KN-fork lift	Fischer RG M8x110	350
FP 130/60S	130KN-fork lift	Fischer RG M8x110	350
FP 155/60S	70KN-fork lift	Fischer RG M8x110	350
FPL 85/27	70KN-fork lift	MMS-plus SS 7,5x80 VZ	350
FPSG 68/.. ES	12,5 kg/mm (*)	MMS-plus SS 7,5x80 VZ	300

The bolt head of MMS-plus SS 7,5\*80 vz. fits into the groove of the corrugation section, too.

The specified length of the screw represents the minimum length given a 20 mm underlining and may be longer, depending on the thickness of the smooth line.

For systems with **long foil** and XA foils (flexible waterproofing slurry / liquid membrane) with heights of 25, 35 and 45mm, countersunk head screws type MMS-plus F 7,5x80 VZ are to be used.

In case that countersunk screws are to be used instead of the hexagon head screws, this must be stated in advance when ordering.

The installation instructions of the manufacturer must be observed.