




- 1 High movement capacity**  
ideal for seismic applications
  - 2 MIGUMAX PopUp system,**  
i.e. cover returns and resets after movement
  - 3 Ideal for use of all types of finishes**  
(granite, marble, ceramic, carpet, vinyl)
- Reduced sightline**  
minimally visible

Expansion joint cover	Joint width max. $b_f \text{ max}$ [mm]	Total movement thermal $\Delta b_f$ [mm]	Total movement seismic $\Delta b_f$ [mm]	Visible width * $b_s$ [mm]	Width infill $b$ [mm]	Width total $b_t$ [mm]	Installation height $h$ [mm]	Height infill max. $h_j$ [mm]	Load bearing capacity 
SDPP 100	100	44 ( $\pm 22$ )	235 (+200/-35)	65	340	510	55	38	pedestrians
SDPP 150	150	44 ( $\pm 22$ )	285 (+200/-85)	65	390	560	55	38	pedestrians
SDPP 200	200	44 ( $\pm 22$ )	335 (+200/-135)	65	440	610	55	38	pedestrians
SDPP 300	300	44 ( $\pm 22$ )	435 (+200/-235)	65	540	710	55	38	pedestrians
SDPP 400	400	44 ( $\pm 22$ )	535 (+200/-335)	65	640	810	55	38	pedestrians
SDPP 500	500	44 ( $\pm 22$ )	635 (+200/-435)	65	740	910	55	38	pedestrians

\* each side

Joint width by the time of installation. Potential tolerance:  $\pm 10$  mm

Side plates and middle section made of solid aluminium with flexible Synca inserts.

Corner versions will be designed individually. Details submitted project-wise on request. Further joint widths available on demand.

**Production length:** 4 m

**Standard colors:** black, grey, beige

