



- 1 Flexible high quality elastomeric insert**  
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Multi directional movement**
- 3 Quick and easy installation**  
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- 4 MultiHole mounting bracket**  
for secure fixing

**Flexible adaptation to site conditions**  
Available with adjustable installation height

Expansion joint cover	Joint width	Total movement	Visible width	Joint width total	Joint height	Load bearing capacity	Load bearing capacity*
	$b_f \text{ max}$ [mm]						
FV 35/15	30	10 (± 5)	35	108	15	30	30
FV 35/20	30	10 (± 5)	35	108	20	30	30
FV 35/25	30	10 (± 5)	35	108	25	30	30
FV 35/35	30	10 (± 5)	35	125	35	30	30
FV 35/50	30	10 (± 5)	35	125	50	30	30
FV 35/4055	30	10 (± 5)	35	108	40, 45, 50, 55	30	30
FV 35/6075	30	10 (± 5)	35	108	60, 65, 70, 75	30	30
FV 35/7590	30	10 (± 5)	35	108	75, 80, 85, 90	30	30
FV 35/90105	30	10 (± 5)	35	108	90, 95, 100, 105	30	30

\* no continuous use

All info on load capacities apply to doweled, not to floating installation.  
For installation in asphalt, please ask for our technical advice.

**Production length:** 4 m

**Standard colors:** black, grey, beige, brown

