



- 1 Flexible high quality elastomeric insert**
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Multi directional movement**
- 3 Quick and easy installation**
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- Flexible adaptation to site conditions**
Available with adjustable installation height
- 4 MultiHole mounting bracket**
for secure fixing

Expansion joint cover	Joint width	Total movement	Visible width	Joint width total	Joint height	Load bearing capacity  [kN]	Load bearing capacity*  [kN]
	$b_f \text{ max}$ [mm]	Δb_f [mm]	b_s [mm]	b_t [mm]	h [mm]		
FV 41/15	35	14 (± 7)	41	114	15	30	30
FV 41/20	35	14 (± 7)	41	114	20	30	30
FV 41/25	35	14 (± 7)	41	114	25	30	30
FV 41/35	35	14 (± 7)	41	131	35	30	30
FV 41/50	35	14 (± 7)	41	131	50	30	30
FV 41/4055	35	14 (± 7)	41	114	40, 45, 50, 55	30	30
FV 41/6075	35	14 (± 7)	41	114	60, 65, 70, 75	30	30
FV 41/7590	35	14 (± 7)	41	114	75, 80, 85, 90	30	30
FV 41/90105	35	14 (± 7)	41	114	90, 95, 100, 105	30	30

No continuous use

All info on load capacities apply to doweled, not to floating installation.
For installation in asphalt, please ask for our technical advice.

Production length: 4 m

Standard colors: black, grey, beige

