



- 1 Flexible high quality elastomeric insert**
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Quick and easy installation**
Solid, but light aluminium brackets for quick installation in floorings with PVC or linoleum coverings (insert with 3 mm upstand, weldable)
- 3 Multi directional movement**
MultiHole mounting bracket for secure fixing
- 4 Flexible adaptation to site conditions**
Available with adjustable installation height

| Expansion joint cover | Joint width | Total movement | Visible width | Joint width total | Joint height | for coverings | Load bearing capacity | Load bearing capacity* |
|-----------------------|------------------------|----------------|---------------|-------------------|------------------|---------------|-----------------------|------------------------|
| | $b_f \text{ max}$ [mm] | | | | | | | |
| FT 35/15 | 30 | 10 (± 5) | 30 | 108 | 15 | 5 | 30 | 30 |
| FT 35/20 | 30 | 10 (± 5) | 30 | 108 | 20 | 5 | 30 | 30 |
| FT 35/25 | 30 | 10 (± 5) | 30 | 108 | 25 | 5 | 30 | 30 |
| FT 35/35 | 30 | 10 (± 5) | 30 | 125 | 35 | 5 | 30 | 30 |
| FT 35/50 | 30 | 10 (± 5) | 30 | 125 | 50 | 5 | 30 | 30 |
| FT 35/4055 | 30 | 10 (± 5) | 30 | 108 | 40, 45, 50, 55 | 5 | 30 | 30 |
| FT 35/6075 | 30 | 10 (± 5) | 30 | 108 | 60, 65, 70, 75 | 5 | 30 | 30 |
| FT 35/7590 | 30 | 10 (± 5) | 30 | 108 | 75, 80, 85, 90 | 5 | 30 | 30 |
| FT 35/90105 | 30 | 10 (± 5) | 30 | 108 | 90, 95, 100, 105 | 5 | 30 | 30 |

No continuous use

All info on load capacities apply to doweled, not to floating installation.

For installation in asphalt, please ask for our technical advice.

Expansion joint covers of series FT 35 are supplied with flush mounted distance insert of FV 35. The top edge of the aluminium joint cover can be used as a screeding guide. The distance insert protects the joint cover until covering is laid. This method avoids damage caused by site traffic.

Production length: 4 m

Standard colors: black, grey, beige

