



- 1 Flexible high quality elastomeric insert**
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Smooth visible surface for easy cleaning**
Antibacterial and physiologically safe
- 3 Quick and easy installation**
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- 4 MultiHole mounting bracket**
for secure fixing
- 5 Flexible adaptation to site conditions**
Available with adjustable installation height

Expansion joint cover	Joint width	Total movement	Visible width	Joint width total		Joint height	Load bearing capacity*	
	$b_f \text{ max}$ [mm]			Δb_f [mm]	b_s [mm]		b_t [mm]	[kN]
FG 35/15	30	6 (± 3)	35	108	15	30	30	
FG 35/20	30	6 (± 3)	35	108	20	30	30	
FG 35/25	30	6 (± 3)	35	108	25	30	30	
FG 35/35	30	6 (± 3)	35	125	35	30	30	
FG 35/50	30	6 (± 3)	35	125	50	30	30	
FG 35/4055	30	6 (± 3)	35	108	40, 45, 50, 55	30	30	
FG 35/6075	30	6 (± 3)	35	108	60, 65, 70, 75	30	30	
FG 35/7590	30	6 (± 3)	35	108	75, 80, 85, 90	30	30	
FG 35/90105	30	6 (± 3)	35	108	90, 95, 100, 105	30	30	

* no continuous use

All info on load capacities apply to doweled, not to floating installation.
For installation in asphalt, please ask for our technical advice.

Production length: 4 m

Standard colors: black, grey, beige, brown

