



- 1 Flexible high quality elastomeric insert**  
Hard wearing, temperature resistant (-30°C to +120°C), replaceable
- 2 Smooth visible surface for easy cleaning**  
Antibacterial and physiologically safe
- 3 Quick and easy installation**  
Solid, but light aluminium brackets for quick installation in screed or tiled floorings
- 4 MultiHole mounting bracket**  
for secure fixing
- 5 Flexible adaptation to site conditions**  
Available with adjustable installation height

Expansion joint cover	Joint width	Total movement	Visible width	Joint width total		Joint height	Load bearing capacity	
	$b_f \text{ max}$ [mm]			$\Delta b_f$ [mm]	$b_s$ [mm]		$b_t$ [mm]	[kN]
FG 41/15	35	6 (± 3)	41	114	15	30	30	
FG 41/20	35	6 (± 3)	41	114	20	30	30	
FG 41/25	35	6 (± 3)	41	114	25	30	30	
FG 41/35	35	6 (± 3)	41	131	35	30	30	
FG 41/50	35	6 (± 3)	41	131	50	30	30	
FG 41/4055	35	6 (± 3)	41	114	40, 45, 50, 55	30	30	
FG 41/6075	35	6 (± 3)	41	114	60, 65, 70, 75	30	30	
FG 41/7590	35	6 (± 3)	41	114	75, 80, 85, 90	30	30	
FG 41/90105	35	6 (± 3)	41	114	90, 95, 100, 105	30	30	

All info on load capacities apply to doweled, not to floating installation.  
For installation in asphalt, please ask for our technical advice.

**Production length:** 4 m

**Standard colors:** black, grey, beige

