

### Fit for traffic with pallet trucks or forklift trucks

Under the condition of sufficient load-bearing capacity of the ground

With solid stainless steel brackets

EPDM insert covers entire joint height

UV/Ozone consistent

High resistancy against chemicals



Slim visible surface

High pressure and deformation resistancy of the EPDM filler material

Smoothed surface for better connection with adjacent flooring

Suitable for subsequent grinding

Reduction of impact noise

Expansion joint cover	Total movement	Visible width	Joint height total	Load bearing capacity	Load bearing capacity
	$\Delta b_f$ [mm]	$b_s$ [mm]	$h$ [mm]	 [kN]	 [kN]
ESF-U 10/20 ES	2 ( $\pm 1$ )	10	20	300	35
ESF-U 10/30 ES	2 ( $\pm 1$ )	10	30	300	35
ESF-U 10/40 ES	2 ( $\pm 1$ )	10	40	300	35
ESF-U 10/50 ES	2 ( $\pm 1$ )	10	50	300	35
ESF-U 10/60 ES	2 ( $\pm 1$ )	10	60	300	35
ESF-U 10/70 ES	2 ( $\pm 1$ )	10	70	300	35
ESF-U 10/80 ES	2 ( $\pm 1$ )	10	80	300	35
ESF-U 10/90 ES	2 ( $\pm 1$ )	10	90	300	35
ESF-U 10/100 ES	2 ( $\pm 1$ )	10	100	300	35

**Production length:** 2.50 m

**Material:** 1.4301 (alloy 304)

**EPDM colours:** black, grey, beige

