

# FA 12

FOR COVERING JOINTS IN WALLS, CEILINGS AND FACADES – SURFACE FIXING

# MIGUTEC

JOINT COVERS FOR EXPANSION JOINTS



- 1 Flexible high quality elastomeric insert**  
Hard wearing, temperature resistant (-30°C to +120°C)
- 2 Large movement capacity**  
Special flexible folded insert for movements up to 20 mm
- 3 High flexibility of insert**  
Suitable for straight and corner joints
- 4 Quick and easy installation**  
Aluminium brackets with cellular rubber sealing strips to compensate for unevenness in the building surface

Expansion joint cover	Joint width	Total movement	Joint width total	Installation height
	$b_f \text{ max}$ [mm]	$\Delta b_f$ [mm]	$b_t$ [mm]	
FA 12/5	75	40 (±20)	132	12
FA 12/7	100	50 (±25)	157	12
FA 12/9	150	100 (±50)	207	12
FA 12/13	200	120 (±60)	257	12
FA 12/14	250	180 (±90)	307	12
FA 12/18	350	200 (±100)	407	12

The expansion joint covers can also be supplied with holes for fixing with screws (distance 300 mm each).

Please state exact details of total joint lengths in your order. The folded insert is then supplied in one piece up to approx. 50 m for the complete joint.

**Production length:** 4 m

**Standard colors:** grey

