

KF 55 / KFE 55

FOR COVERING JOINTS IN WALLS, CEILINGS AND FACADES

MIGUTEC

JOINT COVERS FOR EXPANSION JOINTS



- 1 Perfect optical appearance**
 - 2 Flexible high quality elastomeric insert**
Hard wearing, weather and temperature resistant (-30°C to +120°C)
 - 3 Quick and easy installation**
- Special types of corner joints available**
- Secure and permanent fixing**
using stainless steel spring clips 20 cm each

Expansion joint cover	Joint width max.	Covering Width	Joint depth	
	$b_f \text{ max}$ [mm]	b_t [mm]	h_{min} [mm]	
KF 55/1530	15 - 35	50	40	
KF 55/3560	35 - 60 (15 - 35)	75	50	
KFE 55/1531	20 - 35	47	40	
KFE 55/3561	40 - 60	73	50	

Continuous steel insert and stainless steel clips (5 spring clips will be supplied per running meter).
 Joint covers of series KF 55/1530 and KFE 55/1531 will be normally supplied with the short standard clip K1.
 Joint covers can also be supplied with longer clip K2 $h_{\text{min}} = 75 \text{ mm}$, if desired (at extra charge).
 The KF 55/3560 expansion joint cover is also available with the K1 or K2 clips of expansion joint cover KF 55/1530 for joint width 15 - 35 mm on request. Please state exact details.

Production length: 20 m
Standard colors: grey

