

FA 15 / FA 135

SPECIAL EXPANSION JOINTS FOR SEALING JOINTS
(NOT SUITABLE FOR EXPANSION JOINT)

MIGUTEC

JOINT COVERS FOR EXPANSION JOINTS



1

Special PVC


Long wearing, weather resistant, temperature resistant (-30°C bis +120°C), extensively resistant to oils, acids and bitumen.

Standard version	Joint width max. b_f [mm]	Joint width total b_t [mm]	Corner version	Joint width max. b_f [mm]	Joint width total b_t [mm]	
FA 15/4535	20	45	FAE 15/3035	20	38	
FA 15/5538	25	55	FAE 15/3638	25	49	
FA 135/20	8	27	FAE 135/21	8	30	
FA 135/35	10	35				


Please always test the suitability by conducting a test installation. These expansion joint covers must be glued in the joint to perform. Further special expansion joint covers on request.

Production length: 4 m


Standard colors: grey




FA 15/4535
Material: PVC
Joint width max.: 20 mm




FAE 15/3035 (for corner joints)
Material: PVC
Joint width max.: 20 mm




FA 15/5538
Material: PVC
Joint width max.: 25 mm




FAE 15/3638 (for corner joints)
Material: PVC
Joint width max.: 25 mm



FA 135/20
Material: PVC
Joint width max.: 8 mm



FAE 135/21 (for corner joints)
Joint width max.: 8 mm



FA 135/35
Material: PVC
Joint width max.: 10 mm