

# FS 155

FOR HEAVY DUTY FLOORS

# MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS



- 1** **Symmetrical visible surface has no gaps**  
avoids dirt accumulation
- 2** **Striated surface**  
ensures good skid resistance
- 3** **Articulated telescoping system**  
absorbs movement in 3 directions
- 4** **Solid all-metal expansion joint**  
hard wearing, maintenance-free, long lasting
- 5** **MultiHole mounting bracket**  
for secure fixing

Expansion joint cover	Joint width max. $b_f$ [mm]	Total movement $\Delta b_f$ [mm]	Visible width $b_s$ [mm]	Joint width total $b_t$ [mm]	Joint height $h$ [mm]	Load bearing capacity  [kN]	Load bearing capacity  [kN]	Load bearing capacity  solid plastic tyres [kg/mm]
FS 155/22*	120	40(±20)	155	271	22	600	130	15
FS 155/30	120	40(±20)	155	271	30	600	130	15
FS 155/42	120	40(±20)	157	273	42	600	130	15
FS 155/52	120	40(±20)	157	273	52	600	130	15
FS 155/62	120	40(±20)	157	273	62	600	130	15

\* Minimum joint width 120 mm

**Production length:** 4 m

**Standard colour:** Aluminium

Larger installation heights on request.

