

FS 220 / FS 260 / FS 380

FOR FLOORS WITH SMALL INSTALLATION HEIGHTS

MIGUTRANS

HEAVY-DUTY ALL-METAL JOINT SOLUTIONS FOR LARGE TRAFFIC LOADS



- 1** **Symmetrical visible surface has no gaps**
avoids dirt accumulation
- 2** **Striated surface**
ensures good skid resistance
- 3** **Extremely flat, fixing without arms**
ideal for redevelopment, refurbishment, renovation
- 4** **Articulated telescoping system**
absorbs movement in 3 directions
- 5** **Solid all-metal expansion joint**
hard wearing, maintenance-free, long lasting

Expansion joint cover	Joint width max. b_f [mm]	Total movement Δb_f [mm]	Visible width b_s [mm]	Joint width total b_t [mm]	Joint height h [mm]	Load bearing capacity [kN]	Load bearing capacity [kN]	Load bearing capacity solid plastic tyres [kg/mm]
FS 220/20	60	40 (± 20)	220	220	21	600	130	15
FS 260/20	100	40 (± 20)	260	260	21	600	130	15
FS 380/20	215	40 (± 20)	378	378	21	300	70	15

Production length: 3 m

Standard colour: Aluminium

We recommend fixing with Multi-Monti Stainless steel screws MMS F 7,5 x 95/30 ES (available ex stock), fixing distance: 200 mm.

